



PERDELE SUDURA

PERDELE SUDURA	producator ESAB Suedia
 	<p>Delimiteaza zona de sudare si asigura protectia celorlalti lucratori fata de radiatiile provenite de la procesul de sudare.</p> <p>Realizate in conformitate cu EN 1598 /2002</p> <ul style="list-style-type: none">➤ material ignifugat.➤ factorul maxim de risc : 1 <p><u>Variante constructive :</u></p> <ul style="list-style-type: none">➤ perdea continua sau in fasii➤ material opac (DIN9), sau material transparent (DIN6)➤ culori : rosu, verde <p>Se livreaza cu inele de prindere metalice, ambalate la set de 7 buc.</p> <p>Prevazute cu 7 gauri de prindere a inelelor pe latura orizontala de sus si capse de imbinare pe laturile verticale.</p> <p><u>Dimensiuni</u> (L x H) : 1,4 x 1,8 m</p> <p>Se monteaza la o distanta de minim 2 m fata de zona arcului.</p> <p>Temperatura de depozitare : +10 la +30 °C.</p> <p>Se curata cu apa si detergent.</p> <p><u>Coduri produs :</u></p> <ul style="list-style-type: none">0700 008 004 - rosu inchis transparent0700 008 005 - verde transparent0700 008 006 - verde opac0700 008 001 - rosu inchis transparent /fasii0700 008 002 - verde inchis transparent /fasii0700 008 003 - verde opac /fasii0700 008 007 - inel prindere din PVC0700 008 008 - inel prindere metalic